



**MODEL: H50XT**

All trucks shown with optional equipment. Please refer to quotation specifications.

**CUSTOMER DETAILS**

CUSTOMER	Mt. Diablo Unified School District		
ADDRESS	2326 Bisso Lane, Concord, California, 94520		
SHIP-TO ADDRESS	2326 Bisso Ln, Concord, California, 94520-4802		
CONTACT NAME	Mrs. Laura Warner	TITLE	Transportation Dept
PHONE	+1.925.825.7440		

PROPOSED BY	Ryan Walsh		
PHONE	(510) 661-5700	EMAIL	rwalsh@papemh.com

DATE	May 07 2018	QUOTE EXPIRATION	Jul 06 2018
------	-------------	------------------	-------------



PAPE MATERIAL HANDLING  
 47132 KATO ROAD  
 FREMONT California 94538  
 Phone: (510) 661-5700



## Quoted Model: H50XT Available Features

Hyster® H50XT pneumatic tire lift truck. Nominal 5,000 lb capacity at a 24" load center. The XT series truck represents the Hyster commitment to quality and dependability by incorporating proven designs and systems to ensure productive, efficient operation to satisfy the demands in nearly any application for many years. Stay ahead of your competition with customization that costs you less. With the economical Hyster® XT truck, you'll get access to the same Hyster® Variable Power Technology™ that's in our premium Fortis® series. With this capability, you can customize your performance and fuel efficiency based on your needs. You will be able to run in fuel-efficient mode when production is less demanding, yet switch to a higher performance mode when deadlines are looming. Invest in durable products that reduce downtime. Hyster has engineered a patented stability system that every operator can appreciate. You'll find the Hyster Stability System (HSS®) easier to maintain due to fewer grease points and longer service intervals than the competition. The VISTA™ PLUS mast was designed to maximize visibility for the operator and built strong to have better capacity at higher levels. Leak-free O-ring face seal (ORFS) fittings are used throughout the XT truck series to provide long term reliability and resistance to leaks. Fewer complicated parts means less risk of failure, enhancing uptime for your operation. Everything about the Hyster® XT is tough. Except servicing it. You won't realize the full benefits of the Hyster® XT lift truck until after your first service event experience. That's when its "cowl-to-counterweight" access and one-piece floorplate reveal other engineering advantages designed to keep your truck, and your operation, running smoothly. Configured so you don't have to remove the LP tank to open the hood, the Hyster® XT series is clearly easier for you to service.

## Proposal Summary

Included Items	Description
Model	Hyster® H50XT Lift Truck - 5,000 lb Nominal Capacity, Class V
Powertrain	Brakes - Self Energizing Drum Engine - PSI 2.4L LPG Powershift 1 Speed Transmission
Powertrain Options	High Air Intake Counterweight Rear Exhaust Fixed LPG Bracket with Steel Strap Pressure Sensing Low LPG Fuel Indicator Single Pedal Inch/Brake Arrangement Anti-Clog Radiator Key Switch Start UL Label - Classification Type LP 33.5 lb Steel LPG Fuel Tank with Auxiliary Fill Valve
Mast	3-Stage Full Free Lift Mast, 189" Maximum Lift Height Mast Tilt - 6° Forward / 6° Back
Carriages & Attachments	48" (1220mm) High Load Backrest Extension 42" (1067mm) Wide - Class II - Hook Type Integral Sideshift Carriage
Forks	42" Long x 1.6" Thick x 3.9" Wide (1067mm x 40mm x 100mm) - Class II Hook Type - Standard Taper Forks
Hydraulics	3 Function (1 Auxiliary) Hydraulic Control Valve Mechanical Lever Hydraulic Controls - Cowl Mounted
Hoses	1 Auxiliary Function Hose Group - 2 Hoses Internally Mounted
Wheels & Tires	Drive Tires - 28 x 9-15 - Pneumatic Shaped Solid (PSS) - 2 Layer Construction - Standard Tread Width Steer Tires - 6.00 x 9 - Pneumatic Shaped Solid (PSS) - 2 Layer Construction
Operator Compartment	Document Clip

